

**MISSOURI PUBLIC SERVICE COMMISSION
MANUFACTURED HOUSING DEPARTMENT
APPROVAL OF ANCHORING SYSTEMS**

HOME PRIDE

MODEL	MARK	DESCRIPTION	SOIL TYPE	DUAL STRAP
HP-3	HP-3	Double 4" Helix 3/4" x 30"	2, 3	No
HP-4	HP-4	6" Helix 5/8" x 48"	2, 3, 4	No
HP-5	HP-5	6" Helix 3/4" x 48"	*	No
HP-10	HP-10	36" Cross Drive Rock Anchor	1	No
HP-11	HP-11	48" Cross Drive Rock Anchor	1	No
HP-17	HP-17	Double 4" + 6" Helix 3/4" x 36"	2, 3	No
HP-13	HP-13	J Hook Concrete Anchor	Concrete	
HP-14	HP-14	J Hook Concrete Anchor w/Swivel Head	Concrete	
HP-12	HP-12	Steel Expansion Concrete Anchor	Concrete	
HP-20	HP-20	Double-Slot Buckle Frame Tie		
HP-21	HP-21	Single-Slot Buckle Frame Tie		
HP-22	HP-22	Frame Tie w/Hook		
HP-30	HP-30	Stabilizing Plate		
HP-31	HP-31	Stabilizing Plate		
	Home Pride, Inc.	Galvanized Steel Strapping		
	Home Pride, Inc.	AB Anchor Bolt		
	Home Pride, Inc.	Strap Splice Seal		

STANDARDS FOR INSTALLATION:

- 1) Anchors and all components must be installed per manufacturer's instructions.
- 2) Anchors are approved for designated soil type only.
- 3) One strap per anchor unless the anchor is approved for dual strap use.
- 4) Consult manufactured home set up instructions for number of frame tie downs, over the roof tie downs, and tie down spacing.
- 5) * Approved for soil with a test probe reading of 275 in. lb. and greater.

DATE: October 5, 1998



Steve Jungmeyer
Director
Department of Manufactured Housing,
Recreational Vehicles and Modular Units

The system being used on your home is _____